

STOP Leak[®]

FLASHING TAPE



Handy Pack
Sizes:
50mm x 3m
75mm x 3m

All purpose weatherproof sealing tape

Adheres permanently to clean dry surfaces including:

- ✓ Metals
- ✓ Brick
- ✓ Cement
- ✓ PVC
- ✓ Fibreglass
- ✓ Glass
- ✓ Timber

Roll Sizes:
50mm x 10m
75mm x 10m
100mm x 10m
150mm x 10m
200mm x 10m
300mm x 10m





All purpose weatherproof sealing tape

Stop Leak Flashing Tape is aluminium foil coated with thick rubber/bituminous adhesive used for weathersealing joints and seams. Uses include repairs to roofing, guttering, downpipe or water tank tops, sealing joints around skylights, doors or adjoining building surfaces and weathersealing seams in caravans, trucks, toolsheds etc. Stop Leak Flashing Tape is paintable and one of the most versatile repair tapes available.



Instructions for use:

1. Thoroughly clean and dry surfaces prior to applying Stop Leak Flash Tape.
2. If surface is porous or crumbling, prime with a bitumen primer.
3. Stop Leak Flash Tape may be cut with a knife or scissors.
4. Apply Stop Leak Flash Tape firmly to substrate, smooth down and mould in place.
5. Overlap adjoining strips by a minimum of 25mm.
6. In cold temperatures Stop Leak Flash Tape may be warmed to aid adhesion.



Always wear personal safety protection



Head Office
55 Maurice Road
Penrose, Auckland 1061
Ph 09 622 9100 Fax 09 622 9119

Christchurch 03 365 6453
Palmerston North 06 323 4445

www.dlm.co.nz